

# AMERICAN PRIDE®

## INTERIOR FLAT LATEX PAINT (100 LINE)

### RECOMMENDED USE

For properly prepared interior walls of plaster, wallboard, masonry and tightly adhered wallpaper. Ideal for office buildings, hotel rooms and corridors, nursing homes, schools, hospitals, department stores, apartments, and residences.

This product can be used in occupied areas without typical odor complaints because of the very low odor during application and drying.

### RECOMMENDED APPLICATION

**New Surfaces:**

**Non-Bleeding Wood, Plaster:**

American Pride Interior Latex Primer

**Drywall:**

American Pride Interior Latex Primer

**Metal:**

Not recommended for use on metal door and trim

**Ferrous:** Anti-Rust Primer

**Non-Ferrous:** Galvanized & Aluminum Primer

### RECOMMENDED REPAINT

See Surface Preparation Section.

### EQUIPMENT

<b>Conv. Spray:</b>	40 PSI TIP: 704/FX
<b>Airless Spray:</b>	1800 - 2400 PSI TIP: .015" - .021"
<b>Brush:</b>	Polyester or Nylon
<b>Roller:</b>	3/8" Nap Cover
<b>Pad:</b>	Standard

\*VOC level as determined within the precision of ASTM



This product meets Green Seal environmental standards for volatile organic compounds (VOCs) and other ingredients.

### THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

### LIMITATIONS

- Do not apply when air, surface or product temperature is below 50° F (10° C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90° F (32° C).

### PACKAGING

- Gallons, 5 Gallons

### COLORS

Ready Mix Colors & Tint Bases

### NOTES

Can be used as a performance alternate for Federal Specification TT-P-29K & TT-P-002119 Class I, Flat

### SPECIFICATION DATA

<b>Type:</b>	Acrylic Latex
<b>Finish:</b>	Flat
» Sheen:	5 Max @ 85°
<b>% Solids (varies with color):</b>	
» By Weight:	56 ±2%
» By Volume:	38 ±2%
<b>Wt./Gallon: (White only):</b>	11.86 lbs.
<b>Flashpoint:</b>	212° F (PMCC)
<b>VOC lbs./gal (max):</b>	0*
<b>VOC gm/ltr (max):</b>	0*
<b>Thinner:</b>	Water
<b>Clean-up:</b>	Soap and Water
<b>Dry Time:</b>	
» To Touch:	2 hours
» By Volume:	4-8 hours
» To Service:	Overnight
<b>Thickness:</b>	
» Dry:	1.5 mil
» Wet:	4.0 mil
<b>Coverage:</b>	400 sq. ft./gal (on smooth surfaces)
<b>Flame Spread Rate:</b>	Class A (0-25 on non-combustible surfaces)