

AMERICAN PRIDE®

INTERIOR 100% ACRYLIC SEMI-GLOSS ENAMEL (102 LINE)

American Pride® paints are high performance interior coatings which are low in odor during application and drying. These products are ideal for use in occupied areas because of their low odor and VOC's (Volatile Organic Compounds). Antimicrobial - This product is formulated with an additive that inhibits the growth of microbes on the surface of the paint film. Ceramic Microspheres - This product contains high strength ceramic microspheres to create a tough and stain resistant coating.

RECOMMENDED USE

AMERICAN PRIDE 100% Acrylic Semi-Gloss Enamel is a premium quality paint that is ideal for use in interior applications where a tough, durable, high bonding semi-gloss finish is desired.

Residential: Kitchens, bathrooms, interior doors and trim, and other areas where a tough, washable paint is required.

Commercial: Schools, hospitals, nursing homes, restaurants, office buildings, hotels, stores and apartments.

SURFACE PREPARATION

See Surface Preparation Section on Paint Label.

Drywall:

American Pride® Interior Latex Drywall Primer (AP 801) should be used to seal any unprimed drywall or patching

Plaster:

Allow new stucco, plaster, and masonry to cure 30 days before priming. Use an appropriate primer to seal surfaces before priming

Wallcovering:

Since certain types of wallcovering inks may bleed through this paint, seal the surface with an appropriate stain blocking primer.

Metal / Wood / Paneling:

Prime with an appropriate primer before applying this product

EQUIPMENT

Conv. Spray:	40 PSI TIP: 704/FX
Airless Spray:	1800 - 2400 PSI TIP: .015" - .021"
Brush:	Polyester or Nylon
Roller:	3/8" Nap Cover
Pad:	Standard

*VOC level as determined within the precision of ASTM D3960



This product meets Green Seal environmental standards for volatile organic compounds (VOCs) and other ingredients.

THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

LIMITATIONS

- Do not apply when air, surface or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90°F (32°C).

PACKAGING

Gallons, 5 Gallons

COLORS

- 940 palette colors
- Computer matching available

SPECIFICATION DATA**

Type:	100% Acrylic Latex
Finish:	Semi-gloss
» Gloss: at 60°	38 to 48 (Substrate Dependent)
% Solids (varies with color):	
» By Weight:	53 ±2%
» By Volume:	37 ±2%
Wt./gallon (white only):	11.01 lbs /gal
Flashpoint:	212°F (PMCC)
VOC lbs./gal. (max):	< .05*
VOC grm./ltr. (max):	< 5*
Thinner:	Water
Clean-up:	Soap and Water
Dry Time:	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight
Thickness:	
» Dry:	1.5 mil
» Wet:	4.0 mil
Coverage:	400 sq. ft./gal. (on smooth surfaces)
Flame Spread Rate:	Class A (0-25 on non-combustible surfaces)

**Product Data is based on AP 102-TW